

Mini Multi Dock

Introduce:


This dock comes with 1x USB 3.0 Type-A port + 2x USB-C port + 1x Gigabit Ethernet port, giving access to superfast network speeds. It is compliant with USB 3.0 specification, users can simply connect this dock to the network and all USB peripherals with just a single SuperSpeed USB 3.0 cable. It can increase your desktop and laptop's connectivity with three USB 3.0 ports (1A2C) as well as a Gigabit Ethernet. This dock provides 3 additional USB 3.0/USB 3.1 Gen 1 super speed ports plus a Gigabit Ethernet port. It is great for slim laptops that don't have Ethernet built-in.

This special extension dock can be connected to USB 3.0 (USB 2.0) devices & also USB 3.1 Gen 1 Type-C devices to your computer or laptop, such as USB flash drive, hard disk drive, digital cameras, MP3 players and so on. The Gigabit Ethernet brings a wired internet connection to your laptops, giving you access to a high-speed and reliable network. As a Mini Docking station, it offers connection capability for desktops, notebook PCs, Ultrabooks, game consoles and any embedded system using a standard USB port.


USB-C is a next-generation industry standard, as the year goes on, the new USB-C port is going to begin showing up in more and more devices. As we welcome the new USB-C devices, we've identified a need to bridge the gap between the old, current and new technologies.

Product Features:

- 100% Brand New.
- Provides two USB-C ports, one USB 3.0 Type-A port, and one Gigabit Ethernet port
- Supports USB 3.0/US B3.1 SuperSpeed (5Gbps) transmission, downward compatible with USB 2.0/USB 1.1
- USB-C Port supports data-transfer speed to 5Gbps(USB3.1 Gen 1)
- Supports USB 3.0 Battery Charging V1.2
- Provides overcurrent protection
- Gigabit Ethernet Port, transfer rate speed up to 1000 Mbps
- Supports both Full-duplex with flow control and Half-duplex with backpressure operation
- Supports Network Standards IEEE 802.3az, IEEE 802.3, 802.3u, and IEEE 802.3x
- Supports Wake-On-LAN function, Energy-Efficient Ethernet, Jumbo frames, full duplex flow control
- Supports IEEE 802.1Q VLAN tagging and 2 VLAN ID filtering
- Supports checksum offload IPv4/IPv6/TCP/UDP and TCP Large Send Offload
- Plug and Play Installation for Windows Vista,7,8,8.1,10



Gigabit Ethernet
USB Type-C devices



USB 3.0 Host
USB 3.0/2.0 devices



System requirements:

- Microsoft Windows 10,8.1, 8, 7, vista (32-bit or 64-bit) compatible
- CPU: Intel i3 Dual Core 1.5 GHz / Intel Atom "Bay Trail" Quad Core 1.33 GHz above
- RAM: 2 GB or higher
- need install driver : Mac OS X 10.6 ~ 10.10 , LINUX driver for kernel 3.x

Package Contents:

- Mini Multi Dock X 1
- USB 3.0 AM to BM cable 60CM X 1
- Power Adapter (DC 5V/3.5A) X 1

Specifications:

USB	Upstream port : USB Type B receptacle x 1
	Downstream port: USB 3.0 Type-A receptacle x 1 USB3.1 Type-C receptacle x2 Supports USB 3.1 Gen 1 (5Gbps)
LAN	RJ-45 x 1 (Ethernet 10/100/1000M bit) Transfer Rate: 1000 Mbps (Half Duplex) / 1000 Mbps (Full Duplex) IEEE: IEEE 802.3, 802.3u, 802.3az and 802.3x
Housing	Main body size: 46 x 24 x 65 mm (L x W x H)
	Material: ABS
	Color: Black
Power AC Adapter	Cable length: 60 cm
	Input: AC 100-240V, 50-60 Hz Output: DC 5V/3.5A
Power Mode	Bus-powered for Low Power consumption devices or Self-powered
Working Environment	Operation temperature : 0 ~ 40 °C
	Storage temperature : -20 ~ 70 °C
	Certification : FCC, CE